

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: LAI, Ming-Hsiao

SERIAL NO.:

FILED: Herewith

TITLE: REINFORCED DESIGN OF BATHROOM WALL MOUNTED RACK CONNECTOR

PRELIMINARY AMENDMENT

Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Sir:

In conjunction with the filing of the present application, and prior to an initial Official Action on this matter, please amend the above-identified application as follows:

Preliminary Amendment: SPECIFICATION AMENDMENTS

In Paragraphs [0008] to [0011], please amend the paragraphs as follows:

[0008] FIG. 2 shows an exploded perspective view of the present invention.

[0009] FIG. 3 shows a cross-sectional view of the present invention.

[0010] FIGS. 4-5 show the cross-sectional views of another lateral of bolt and fillister.

[0011] FIG. 6-7 show ~~the assemble~~ perspective views of the assembled bathroom wall mounted rack.

In Paragraphs [0013] to [0018], please amend the paragraphs as follows:

[0013] As shown in FIGS. 1-3, there is a bathroom wall mounted rack embodied in the present invention ~~comprises~~.

[0014] The present invention includes a wall mount 10, with wall end 11 as one end. Holes are set on the wall mount 10 and fixed on the wall end by bolts 05. In the center of wall mount, one frame is perforated by frame holes 13 to the wall end 11. In addition, a cover 06 may be set on the outside in front of wall mount 10 to conceal different bolts in a purpose of prettification; ~~and~~.

[0015] There is also a fillister 14, installed on two opposite sides of the wall end 11 of wall mount 10 and the frame holes 13;

[0016] The present invention also has a frame 20, without fixed pattern, such as towel rack, tissue rack, soap rack and handle rack, etc. The connector end 21 of frame 20 just goes through the frame holes 13 on the frame in the center of wall mount 10 mentioned above; ~~and~~.

[0017] There is a through hole 22, set on the connector end 21 of frame 20 in the condition of radial transfixion. The two ends of through hole 22 are corresponding to the fillisters 14 of wall mount 10;
[0018] The invention further includes a bolt 30 going through the through hole 22 of frame 20 connector end 21. The two ends protrude on two sides of frame 20 connector ends 21 and further embed into two fillisters 14 of wall mount 10 correspondingly so as to connect and fix the frame 20 and the wall mount 10.

IN THE ABSTRACT

On page 7, please amend the Abstract as follows:

A bathroom wall mounted rack ~~comprises~~ has mounts with a wall end as one end; holes set on the wall mount, and in the center one frame is perforated to the wall end; ~~through.~~ Through holes are set on the connector end of frame in the condition of radial transfixion; and the two ends of through hole are corresponding to the fillisters of wall mount; ~~bolts going.~~ Bolts go through the through hole of frame connector end, the two ends protrude on two sides of frame connector ends and further embed into two fillisters of wall mount correspondingly so as to connect and fix the frame and wall mount. Therefore, the combination and orientation design of bolts will enable the frame to have an effect of firm support and orientation to actually avoid from circumvolution, loose and split so as to meet the advancement requirements of more firmness and durability.